



One Fire-Lite Place  
Northford, CT 06472-1653 USA

203-484-7161  
203-484-1098 Fax

## PRODUCT RETIREMENT ANNOUNCEMENT

### System Sensor 400 Series Conventional Models replaced by i<sup>3</sup> and 2151 photoelectric plug-in heads.

January 29, 2005

Dear Valued Customer,

Our sister company and business partner, System Sensor continuously evaluates the demand for our mutual product lines, and has found the conventional 400 series photoelectric smoke detectors to represent a relatively low level of need for our customers. Compounding this situation is the upcoming obsolescence of a critical component to the 400 series by their vendor. Consequently, System Sensor will in turn discontinue these products. **The immediate retirement pertains to UL listed models in the US only.** The replacement product for these smoke detectors will be the model 2151 photoelectric plug-in smoke detector head and the i<sup>3</sup> series photoelectric smoke detectors.

The model 2151 and i<sup>3</sup> series are highly successful detectors that we have carried for many years. In order to support installations requiring the model 2151 plug-in smoke detector head the 400 series bases are not being discontinued. Datasheets for both the model 2151 and i<sup>3</sup> series can be downloaded from [www.firelite.com/datasheets](http://www.firelite.com/datasheets). The pricing for the model 2151 detector and i<sup>3</sup> series can be found in your FireLite price book.

**Please anticipate any future needs for the conventional 400 series photoelectric smoke detectors and place your final orders by April 15, 2005. The conventional 400 series photoelectric smoke detectors will no longer be manufactured after April 15, 2005.**


The following table on the next page outlines the 400 series models being retired, and 2151 and i<sup>3</sup> models to use in replacement..

400 Series Models Being Retired	Replacement 2151 & i <sup>3</sup> Series Models
2400	2W-B
2400TH	2WT-B
2412B	4W-B
2412THB	4WT-B
2424	4W-B
2424TH	4WT-B
2451	2151
2451TH	2WT-B or 4WT-B

SHOULD THE NEED ARISE TO MODIFY AN EXISTING SYSTEM OF 400 SERIES MODELS PLEASE CONTACT FIRELITE TECHNIAL SERVICE. FOR APPLICATIONS REQUIRING THE SMOKE DETECTOR TO SWITCH 120 VAC CONTROL CIRCUITS, THE MODEL 2151 SMOKE DETECTOR HEAD WITH 100 SERIES RELAY BASE OR 400 SERIES RELAY BASE WITH THE F110 FLANGE SHOULD BE USED.

We appreciate your cooperation during this transition period. Should you have any questions regarding this announcement please contact FireLite technical support.

Sincerely,



Nick Martello  
FireLite Marketing Director